# PRODUCT SPECIFICATIONS / INFO



1	11	
T		
-	_	

6

# **IPP15-1LW**

#### Description

Manual-On Occupancy Sensor, 1800W@120VAC INC, 1800VA@120 VAC FL, 1/2 HP, 60Hz, for single pole or 3-way applications when used with IPP0R or VZ0SR, 180 Degree, 900 Sq. Ft. Coverage, Decora Passive Infrared Wall Switch- White, California Title 24 2005 Compliant

UPC Code: 07847729390

# **Product Features**




Switch Type: Single-Pole & 3-Way Manual ON Adjustment: Manual Sensor Technology: Passive Infrared Pattern Degrees: 180 Coverage Range Sq. Ft.: 900 Time Adjustment: 30s-30m Load Rating: 1800W@120V INC 1800VA FL Voltage: 120 Volt AC 60Hz Neutral: Required Color: White Standards and Certifications: UL/CSA Warranty: 5-Year Limited Code Compliance: California Title 24 2005

# **Features and Benefits**

- Manual-ON/Automatic OFF operation in accordance with California Title 24 2005 requirements
- Low-Profile design eliminates an obtrusive "scanning device" look. Elegant Decora styling compliments any interior and coordinates with leviton's popular line of Decora wiring devices
- 180 degree field-of-view provides approximately 900 square feet of coverage suitable for bathrooms, basements, garages, utility rooms and a variety of other residential areas
- Convenient push-button provides Manual ON/OFF light switching at any time
- Segmented fresnel lens provides optimum sensitivity and performance. It is designed with an extensive "minor motion" area where even slight body movements will be detected
- Horizontal field of view may be adjusted between 180 and 32 degrees of arc by using internal blinders located on either side of the lens
- Four optional manual adjustments for delayed-OFF time settings maximize energy savings: 30 seconds (for walking test), 10 minutes, 20 minutes and 30 minutes
- · LED Indicator Light flashes when sensor detects motion to verify detection is active
- Unit can be used for 120V lighting. Compatibile with both electronic and magnetic ballasts or 1/2 HP loads
- Relay switches at zero crossing point of the AC power curve to ensure maximum contact life and compatibility with electronic ballasts
- Fits in standard wallbox and replaces single-pole wall switch, 3-Way operation when used with IPP0R Series Remote Sensor or Vizia Switch Remote
- Requires a neutral (white) wire connection
- UL Listed and CSA Certified, complies with California Title 24 2005 Energy Code and FCC regulations
- · Five-Year Limited warranty

Packaging Specifications			
Standard Pack	· · · · · · · · · · · · · · · · · · ·		
Inner Pack			
Unit Pack			
Carton Length			
Carton Width			
Carton Depth	5.5		
Cube			
Carton Weight	4.07		

# Field of View (in feet)



30 ft. (9.1m)

TOP VIEW

# SIDE VIEW

# SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:		
JOB NUMBER:			

# Leviton Manufacturing Co., Inc.

59-25 Little Neck Parkway, Little Neck, NY 11362-2591 Telephone: 1-800-323-8920 · FAX: 1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): 1-800-824-3005

Leviton Manufacturing of Canada, Ltd. 165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: 1-800-469-7890 · FAX: 1-800 -824-3005

# Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

# Visit our Website at: www.leviton.com

©2007 Leviton Manufacturing Co., Inc. All rights reserved. Subject to change without notice.

